
Specification

FOR FTTH Drop Cable GJXH

1. CABLE CONSTRUCTION

1.1. CROSS SECTIONAL DIAGRAM



1.2. STRUCTURE SPECIFICATION

Cable Type	GJXH		
Fiber count	2F		
Strength Member	0.45mm steel		
Jacket Material	LSZH Black UV Resistant		
OD of cable(mm)	2.0×3.0±0.2		
Net weight (kg/km)	10±2		
Max.Tensile Loading (N)	120		

1.3 Fiber identification

NO.	1	2	3	4	5	6	7	8	9	10	11	12
Fiber Color		Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Pink	Aqua

JDM NETWORKNG

2.Performance Parameters Of the Optical Fiber

2.1 Single Mode Fiber

LTEMS	UNITS	SPECIFICATION G657A				
Fiber type						
Attenuation	dB/km	1310nm≤ 0.35				
		1550nm≤ 0.21				
		$1310 \text{nm} \le 3.6$				
Chromatic Dispersion	ps/nm.km	1550nm≤ 18				
		1625nm≤ 22				
Zero Dispersion Slope	ps/nm².km	≤ 0.092				
Zero Dispersion Wavelength	nm	1300 ~ 1324				
Cut-off Wavelength (λcc)	nm	≤ 1260				
Attenuation vs. Bending	ID.	(10mm radius, 1ring)≤ 1.5 @				
(60mm x100turns)	dB	1625nm				
Mode Field Diameter	μm	9.2 ± 0.4 at 1310nm				
Core-Clad Concentricity	μm	≤ 0.5				
Cladding Diameter	μm	125±0.7				
Cladding Non-circularity	%	≤ 0.8				
Coating Diameter	μm	245±5				
Proof Test	Gpa	≥ 0.69				

2.2 Fiber optical cable bending radius

Static bending: ≥ 15 times than cable out diameter

Dynamic bending: \geq 20 times than cable out diameter.

3. Mark and Package


3.1 Cable Mark

- 3.1.1 Manufacturing year, fiber count, fiber type, sheath material, meter mark for without especial request.
- 3.1.2 Customized printing by order request.

JDM NETWORKNG

3.2 Drum Mark

- 3.2.1. Drum size according to the length of cable packed.
- 3.2.2. Logo will be print on both side of drum, size will be according to customer request.
- 3.3.3. Label including manufacturing date, item number, length, description of cable, drum number.



3.3 Package

- 3.3.1 Packing length, 1km/plywood reel, the other length packed available.
- 3.3.2 Packing material, cable on drum wrapped by protective foil with, Plywood reel as usual package, metal reel available but shall be noted individually if required specially.